

State of California  
AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-4-40

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

DEERE POWER SYSTEM GROUP OF DEERE & COMPANY

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Deere Power System Group of Deere & Company 1998 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

Typical Equipment Usage: Tractor, Generator Set, and Other OEM Products

Fuel Type: Diesel

<u>Engine Family</u>	<u>Displacements in Liters</u>	<u>Exhaust Emission Control Systems and Special Features</u>
WJDXL08.1009 (450TA)	8.1	Turbocharger

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matters (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

<u>Exhaust Emissions (g/bhp-hr)</u>				<u>Smoke Opacity ( % )</u>		
<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
1.0	8.5	6.9	0.4	20	15	50

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

<u>Engine Family</u>	<u>Exhaust Emission (g/bhp-hr)</u>				<u>Smoke Opacity ( % )</u>		
	<u>THC</u>	<u>CO</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	<u>Lug</u>	<u>Peak</u>
WJDXL08.1009 (450TA)	0.6	1.6	6.2	0.2	12	11	17


BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures--Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels--1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this 17<sup>th</sup> day of February 1998.

  
R. B. Summerfield, Chief  
Mobile Source Operations Division

# LARGE ENGINE MC \_L SUMMARY

Process Code: **New Submission**

Manufacturer: **Deere Power Systems Group of Deere & Company**

Manufacturer Family Name: **450TA**

EPA Engine Family: **WJDXL08.1009**

8. Fuel Rate:  
(lbs/hr)@peak torque  
Device Per SAE J1930

7. Fuel Rate:  
mm/stroke@peak  
torque

6. Torque @ RPM  
(SEA Gross)

5. Fuel Rate:  
(lbs/hr) @ peak HP  
(for diesels only)

4. Fuel Rate:  
mm/stroke @ peak HP  
(for diesel only)

3. BHP@RPM  
(SAE Gross)

1. Engine Code 2. Engine Model

6081TF001A	217@2200	109@2200	80@2200	678@1200	147@1200	59@1200	EM, TC
6081TF001B	200@2200	101@2200	74@2200	623@1300	130@1300	56@1300	EM, TC
6081TF001C	211@1800	127@1800	76@1800	N/A	N/A	N/A	EM, TC
6081TRW01	161@2100	84@2100	58@2100	563@1440	114@1400	52@1400	EM, TC
6081TRW02	181@2100	95@2100	65@2100	637@1400	125@1400	57@1400	EM, TC
6081TDW01	172@2200	88@2200	64@2200	573@1400	116@1400	54@1400	EM, TC
6081TF001D	172@2200	88@2200	64.4@2200	573@1400	116@1400	53.8@1400	EM, TC

U-R-4-40